

CMT320

4G router with built-in 5 dBi antennas, two Fast Ethernet ports and DC or PoE input.

Cellular Router

Radio and wireless

Cellular module	EC200A-EU 4G LTE module
SIM	1 x Nano SIM slot
Cellular antennas	2 x built-in antennas, 5 dBi each
Wi-Fi frequencies	2.400 GHz to 2.484 GHz
Wi-Fi standard	IEEE 802.11b/g/n
Wi-Fi speed	Up to 300 Mbps at 2.4 GHz
Wi-Fi antennas	2 x built-in antennas, 5 dBi each
Transmit power	< 20 ± 2 dBm at 2.4 GHz

Interfaces

WAN	1 x 10/100 Mbps adaptive Ethernet port
LAN	1 x 10/100 Mbps adaptive Ethernet port
Controls	Reset button; hold for 6 to 10 seconds to restore factory settings
Indicators	Power, WAN, LAN, Wi-Fi and 4 x cellular signal LEDs

Power and mechanical

Power input	12 V DC / 1 A or 24 V PoE / 0.5 A
Power consumption	< 12 W
Dimensions	198 x 86 x 40 mm
Net weight	0.24 kg

Environment and compliance

Operating temperature	-30 °C to 55 °C
Storage temperature	-40 °C to 70 °C
Operating humidity	5% to 95%, non-condensing

Confirm the model, hardware version and supplied accessories before ordering.