

EAP300

AX3000 outdoor AP with four directional antennas, Gigabit uplink and IP67 protection.

Outdoor Access Point

Radio and wireless

Wi-Fi frequencies	2.400 GHz to 2.484 GHz; 5.150 GHz to 5.850 GHz
Wi-Fi standard	2.4 GHz: IEEE 802.11b/g/n/ax; 5 GHz: IEEE 802.11a/n/ac/ax
Wi-Fi speed	Up to 574 Mbps at 2.4 GHz; up to 2402 Mbps at 5 GHz
Wi-Fi antennas	4 x built-in directional antennas

Interfaces

WAN	1 x Gigabit Ethernet, 48 V PoE input
Console	1 x console port
Controls	Reset button; hold for 6 to 10 seconds to restore factory settings
Indicators	Power, system, WAN, 2.4 GHz and 5 GHz LEDs

Power and mechanical

Power input	IEEE 802.3at PoE
Power consumption	< 16 W
Dimensions	304 x 181 x 88 mm
Net weight	1.6 kg

Environment and compliance

Protection	IP67
Operating temperature	-30 °C to 55 °C
Storage temperature	-40 °C to 70 °C
Operating humidity	5% to 95%, non-condensing

Confirm the model, hardware version and supplied accessories before ordering.