

GWTX10

Five-port Gigabit gateway with four PoE outputs, USB 3.0 and AP management.

Gateway | Reference 1.0 | 2026-09-06 | Reference specification - confirm the ordered hardware configuration.

Interfaces

Ethernet	5 x Gigabit RJ45: 1 x WAN and 4 x LAN
PoE output	4 x IEEE 802.3at/af outputs; up to 30 W per port; 55 W total budget
USB	1 x USB 3.0 port

Platform and functions

AP management	Up to 200 access points; Captive Portal
Processor	880 MHz dual-core CPU
Memory	16 MB NOR flash; 256 MB DDR3 RAM

Power and mechanical

Power input	54 V DC / 1.11 A; IEEE 802.3at/af PoE or 24/48 V passive PoE
Max power consumption	60 W including PoE output
Without PoE load	5 W
Idle power consumption	2 W
Installation	Desktop / Wall-mount
Casing	Metal
Dimensions	190 x 100 x 28 mm
Net weight	454 g

Environment and compliance

Operating temperature	0 °C to 40 °C
Storage temperature	-40 °C to 70 °C
Operating humidity	5% to 95%, non-condensing
Storage humidity	0% to 100%, non-condensing
Certifications	FCC, CE

Confirm compatible access points, controller software and the available PoE output budget for the selected power input.

Confirm the model, hardware version and supplied accessories before ordering.